

[Download](#)



Sep 1, 2019 Try using the software from a different computer or with a different . It is required to register the key and software to the server machine so the license can be acquired. To register the HASP dongle with the software . See Support page for more information. Thank you. Sep 4, 2019 A JTAG adapter is an electronic device that provides the ability to control another electronic device using a program running on a computer. You can use a JTAG adapter to debug and modify code within an ARM processor, in conjunction with a debugger software such as CodeRED, BlueKat and IceDragon. A JTAG adapter provides the ability to make modifications to an ARM chip that are not normally available. UoN is an open source, distributed, cross-platform product developed by the Engineering and Research Department (ERN) of the UoN Division for the Department of Engineering University of Navarra. UoN is available in English, Spanish, and Catalan. A detailed report of the UoN project can be found in the report: Evaluation of the iCAT Library for the Development of Cross-Platform Image Acquisition and Reconstruction Software by Isac Tejada-Carvajal and Juan Manuel Garrido. Sep 5, 2019 If you are using a Windows 10 Insider version: we recommend that you use the version of Windows from the Windows 10 October 2019 Update (version 1909). If you are using Windows 7 or 8: we recommend that you use the version of Windows from the Windows 7 April 2019 Update or the Windows 8.1 October 2018 Update. If you are using a Windows 10 version older than the September 2019 Update: we recommend that you upgrade to Windows 10 version from the Windows 10 October 2019 Update (version 1909). Sep 4, 2019 In some situations the JTAG adapter is not recognized. In this case, we recommend that you connect the JTAG adapter to a different USB port or power on your computer while the JTAG adapter is connected to the USB port. After unplugging the JTAG adapter, reconnect it to the same USB port to continue using UoN. Thank you. Sep 1, 2019 You need to allow the exception to access the port in order to connect the adapter. S-MAC devices can be used to bypass cable firewalls (such as Firebox) without IP or MAC address filtering. Make sure the following USB exceptions are added to the Windows firewall:

If you have tried all the solutions above and your dongle is still not working. You can contact our technical support team at hasp-keys@templetons.com . Nov 27, 2018 Not able to connect the key. If you are using the USB driver supplied by Webhotel you need to disable Secure Boot. In my case, I had to use the Signature Edition driver in the Device Manager. Download the HASP Signature Edition Driver from this page . Open the BCD file located in the downloaded.zip package and double-click on Hasp-Signature. Click on the icon for an offline.exe file and save it on your desktop. . Run the.exe file. To make sure the installation is successful, you should see the following message: The installation will now start. Once the installation is finished, the Startup entry should look like this: If you get the following message: In this case you need to press CTRL+ALT+DEL to open the task manager. Select the Startup tab in the task manager, and delete or disable the service that is using the dongle. After making sure you did this, restart your machine and try again to connect the key. Jan 16, 2019 Windows 10 Pro v 1809 broke the HASP key driver. I am using a newer version. When connecting the HASP key to Windows 10 Pro v 1809, I receive the following error: "This device can not be used with this version of Windows" If you are using v1809 and receive the same error, try running the Hasp windows driver installer and choose "Install these components only". Oct 9, 2019 If you are using Windows 10 v1903 and earlier versions you can uninstall this driver: On the desktop click the Windows Button (top left), then press the X in the top-right corner of the window that opens. Then press the Refresh or Close button. The driver should be listed here. Right-click on it and select Uninstall. The driver will now be removed from the system. Oct 20, 2019 The company that makes this dongle (Hasp key) issued a firmware update for some models. They are still working on the update to the version 11. Nov 6, 2019 When you do the 1-time internet activation with a connection for 6 hours on 2d92ce491b